

100LB50PHNCVLN060002

100W/LED HBPRIS/VL/5000K GEN2



Ambient Temp. Range: -40 to 122 °F

Average Life Hours: 50000

Beam Angle: 103

Color: Black/Silver

CRI: 80

Dimmable: Yes

Fixture Watts: 100.0

Lamp Type: LED

Material: Die Cast Aluminum

Mounting: Hook

Package (LxWxH): 19.25 IN x 19.25 IN x 16.00 IN

Power Factor: 0.9

Power Source: LED Driver

Shape: Low Bay

Style: 100W LED Low Bay, High Bay Prismatic, No Lens Cove, 120-277V

Type: 100W LED Low Bay, High Bay Prismatic, No Lens Cover

Voltage: 120-277 V

Width: 16.50 IN

Application: Low Bay Lighting

Driver Type: LED Driver

Bulb: LED

Color Temperature: 5000K

Diameter: 16.50 IN

Fixture Type: 100W LED Low Bay, High Bay Prismatic, No Lens Cove, 120-277V

Frequency Rate: 50/60

Length: 19.25 IN

Lumens: 11660

Number of Lamps: 1

Package Weight: 32.25 L

Pack By: 1

Reflector Type: Prismatic

Special Features: 6" Cord

Temperature Range: -40 to 122 °F

UPC: 726585100040

Wattage: 100.0 W

CULUS,UL Damp Location,ROHS,DLC,Lighting Facts