shat·r·shield lighting inc.

100LB50PHNCVLN060002

100W/LED HBPRIS/VL/5000K GEN2

Ambient Temp. Range: -40 to 122 ºF

Application: Low Bay Lighting

Average Life Hours: 50000

Driver Type: LED Driver

Beam Angle: 103

Bulb: LED

Color: Black/Silver

Color Temperature: 5000K

CRI: 80

Diameter: 16.50 IN

Dimmable: Yes

Fixture Type: 100W LED Low Bay, High Bay Prismatic, No Lens Cove, 120-277V

Fixture Watts: 100.0

Frequency Rate: 50/60

Lamp Type: LED

Length: 19.25 IN

Material: Die Cast Aluminum

Lumens: 11660

Mounting: Hook

Number of Lamps: 1

Package (LxWxH): 19.25 IN x 19.25 IN x 16.00 IN

Package Weight: 32.25 L

Power Factor: 0.9

Pack By: 1

Power Source: LED Driver

Reflector Type: Prismatic

Shape: Low Bay

Special Features: 6" Cord

Style: 100W LED Low Bay, High Bay Prismatic, No Lens Cove, 120-277V

Temperature Range: -40 to 122 ºF

Type: 100W LED Low Bay, High Bay Prismatic, No Lens Cover

UPC: 726585100040

Voltage: 120-277 V

Wattage: 100.0 W

Width: 16.50 IN

CULUS,UL Damp Location,ROHS,DLC,Lighting Facts