shat:r:shield lighting inc.

100LB50PLLCVLN060002

100W/LED LB FIX/VL/LC/5000K GEN2



Ambient Temp. Range: -40 to 122 PF

Average Life Hours: 50000

Beam Angle: 103
Color: Black/Silver

CRI: 80

Dimmable: Yes

Frequency Rate: 50/60

Lamp Type: LED Length: 12.75 IN Lumens: 10000

Number of Lamps: 1

Package Weight: 32.25 L

Pack By: 1

Reflector Type: Prismatic

Special Features: Bottom Lens, 6' Cord

Temperature Range: -40 to 122 °F

UPC: 726585604258 **Wattage:** 100.0 W

CULUS, UL Damp Location, ROHS, DLC, Lighting Facts

Application: Low Bay Lighting

Driver Type: LED Driver

Bulb: LED

Color Temperature: 5000K

Diameter: 16.50 IN

Fixture Type: 100W LED Low Bay, Prismatic With Lens

Cover, 120-277V

Height: 18.50 IN

Lamp Wattage: 100

Material: Die Cast Aluminum

Mounting: Hook

Package (LxWxH): 19.25 IN x 19.25 IN x 16.00 IN

Power Factor: 0.9

Power Source: LED Driver

Shape: Low Bay

Style: 100W LED Low Bay, Prismatic with Lense Cover,

120-277V

Type: 100W LED Low Bay, Prismatic with Lense Cover,

120-277V

Voltage: 120-277 V