

shat·r·shield lighting inc.

200WDHB50VL1200000000001N

200W/WDHB/5000/VL/120 DEG



Ambient Temp. Range: -22 to 122 °F

Average Life Hours: >50,000

Beam Angle: 120

Color Temperature: 5000K

Dimmable: 0-10V

Height: 7.88 IN

Length: 19.25 IN

Mounting: HOOK, SURFACE, NPT ADAPTER

Package Weight: 20.60 L

Pack By: 1

Size (LxWxH): 19.25 IN x 19.25 IN x 7.88 IN

Temperature Range: -22 to 122 °F

Voltage: 120-277 V

Width: 19.25 IN

Application: Industrial, Commercial, Food Processing, Cosmetic, Pharmaceutical

Driver Type: LED Drive

Color: Grey

CRI: 80

Frequency Rate: 50-60

Lamp Type: LED

Lumens: 26000

Package (LxWxH): 22.00 IN x 10.00 IN x 23.00 IN

Power Factor: 0.9

Reflector Type: Clear Polycarbonate

Special Features: NSF Wash Down

UPC: 726585381142

Wattage: 200.0 W

CULUS,UL Wet Location,ROHS,NSF Non-Food Zone,NSF Splash Zone,IP66,IP69K,DLC,Lighting Facts