



Classic LED High Bay/ Low Bay

The Classic LED High Bay Fixtures are high efficiency retrofits for antiquated HID lamps. The 280W fixture is ideal in applications with ceiling heights above 30 feet and the 200W is ideal for those above 20 feet. At 110+ lumens per watt, the LED High Bays are direct 1-to-1 replacements for 400W metal halides. **Traditional Design** - Aesthetically similar to standard HID fixture style. **Excellent ROI** - Return on investment is typically less than 1.5 years, depending on local utility rebates. **Durable** - Thick polycarbonate lens protects LED chips. **Prismatic or Aluminum Reflector** options for desired beam spread **Cast Aluminum Driver Heat Sink** - Cooling fins on the housing provide optimum heat management for the driver to prolong the life of electronics. **Extruded Aluminum LED Heat Sink** - Dissipates heat from the LEDs electronics to maximize thermal management and LED life.

Specifications:

- 280W / 32,500 Lumens / 5000K / 80 CRI
- 200W / 22,800 Lumens / 5000K / 80 CRI
- Universal Driver: 120-277V; 347-480V available
- Dimming: 0-10V
- L70 > 55,000 Hours, Power Factor > 0.9
- Operating Temp: -40°F to 122°F (-40°C to 50°C)
- Weight: 20 lbs. (9.07kg)
- Warranty: 7 year limited
*(*280W is 7 year limited at 40°C and 5 year limited at 50°C)*

The Classic LED Low Bay Fixtures are used in applications where ceiling heights are below 20 feet and at 120 lumens per watt, are a direct 1-to-1 replacement for 175W metal halides. **Traditional Design** - Aesthetically similar to standard HID fixture style. **Excellent ROI** - Return on investment is typically less than 1.5 years, depending on local utility rebates. **Durable** - Thick polycarbonate lens protects LED chips. **Prismatic or Aluminum Reflector** options for desired beam spread **Cast Aluminum Driver Heat Sink** - Cooling fins on the housing provide optimum heat management for the driver to prolong the life of electronics. **Extruded Aluminum LED Heat Sink** - Dissipates heat from the LEDs electronics to maximize thermal management and LED life.

Specifications:

- 100W / 12,000 Lumens / 5000K / 80 CRI
- Universal Driver: 120-277V; 347-480V available
- Dimming: 0-10V
- L70 > 55,000 Hours, Power Factor > 0.9
- Operating Temp: -40°F to 122°F (-40°C to 50°C)
- Weight: 20 lbs. (9.07kg)
- Warranty: 7 year limited

Applications: Processing Plants, Cold Storage, Packaging Plants, Warehouses, Manufacturing, Hangars, Industrial Facilities, Sports Complexes, Gymsnasiums

Certifications: DLC, cULus, CSA, RoHS, UL Wet Location

