

The logo for Shat-R-Shield Lighting Inc. features a stylized orange and black grid icon to the left of the company name. The name "shat·r·shield lighting inc." is written in a bold, lowercase, sans-serif font, with "shat·r·shield" in black and "lighting inc." in a lighter grey.

# 06661E

LED/12W/T8/48/850-G9DM (PK30)

**Ambient Temp. Range:** -20 to 45 C

**Average Life Hours:** 50000

**Base:** Medium Bi-Pin (G13)

**Coating:** Copolymer

**CRI:** 80

**Dimmable:** No

**Fixture Type:** Dual Mode

**Lamp Type:** Linear LED

**Lens Material:** Glass

**Package (LxWxH):** 49.80 IN x 6.50 IN x 7.90 IN

**Pack By:** 30

**Shape:** T

**UPC:** 726585225897

**Wattage:** 12.0 W

**Application:** Commercial, Hospitality, Education, Healthcare, Retail, Residential

**Ballast Type:** Dual Mode

**Bulb:** T8

**Color Temperature:** 5000K

**Diameter:** 1.00 IN

**Finish:** Frosted

**Initial Lumens:** 1900

**Length:** 48.00 IN

**Mean Design Lumens:** 1900

**Package Weight:** 16.65 L

**Power Source:** Internal Driver

**Special Features:** Shatter-Resistant

**Voltage:** 120-277 V

ULEPH,UL 2007A,ROHS,NSF Non-Food Zone,NSF Splash Zone