



IRONCLAD® LDL

LIGHT DUTY LINEAR

The Ironclad® Light Duty Linear is a durable, easy-to-install LED fixture for area, walkway, or task lighting. It can be used alone or linked in-line and is built to resist moisture, dust, chemicals, and corrosion. Rated IP69K/IP66 for wash-down resistance, IK10 for impact protection, and certified NEMA4X, NEMA5, UL Wet Location, and UL1598.

Specifications:

- **Lumens:** 2700, 6800 lm
- **Watts:** 20W, 50W
- **Voltage:** 120-277 VAC 50/60 HZ
- **Operating Temp:** -22°F to 104°F (-30°C to 40°C)
- **LED Life:** L70>54,000 Hours; Projected>100,000 Hours
- **Lens:** 2.75" Diameter Polycarbonate Frosted Lens in 2FT and 4FT lengths
- **Installation:** Surface mount or suspended mount; Standalone or Daisy Chained
- **Mounting:** .125" aluminum heat sink to maintain thermal management.
- **Dimensions:** 20W/ 23" Long, 50W/54" Long x 2.75"
- **Color Temperatures:** 5000K, 4000K (custom order only)
- **Warranty:** 5 year limited

Certifications: cULus, IP69K, IP66, IK10, IK8, NEMA4X, NEMA5, UL Wet Location, UL1598