



30083

F40T12 CW SUPREME/ALTO (PK X 30)



Ambient Temp. Range:		Amps:	
Application:	Industrial, Food Processing, Food Service, Retail, Hospitality, General Lighting	Average Life Hours:	24000
Ballast Type:		Base:	Medium Bi-Pin (G13)
Battery:		Beam Angle:	
Bulb:	T12	Coating:	Copolymer
Color:	Cool White	Kelvin:	4100 K
Construction:		CRI:	89
Diameter:	1.50 IN	Dimmable:	
Effective Arc Length:		Enclosure:	
Environmental Conditions:		Filament Type:	
Finish:		Fixture Type:	
Fixture Watts:		Field Wiring:	
Focus:		Frequency Rate:	
Height:		Housing Color:	
Housing Material:		Housing Finish:	
Incan Wattage Equivalent:		Initial Lumens:	2600
Pack By:	30	Weight:	0.767
Inventory Specification:		Lamp Type:	Fluorescent
Lamp Wattage:		Length:	48.00 IN
Lens Material:		Light Center Length:	
Material:		Mean Lumens:	2250
Mount:		SDS:	Download SDS
Number of Lamps:		Operating Position:	
Package Dimensions:	49.50 x 8.75 x 10.25	Package Weight:	23.35 L
Power Factor:		Power Rating:	
Power Sources:		Radiation Specification:	
Reflector Type:		Shape:	T
Size:		Socket Type:	
Special Features:	Shatter-Resistant	Start Type:	
Style:		Temperature Range:	
Total Harmonic Distortion:		Type:	Straight Linear Fluorescent Lamp

UNSPSC:	39101605	UPC:	726585300839
Volts:		Wattage:	40.0
Width:		Warm Up Time:	
ProdCI:	01		

ULEPH,ROHS,NSF Non-Food Zone,NSF Splash Zone