

F60T12 CW/HO/ALTO/TSC (PK X 15)



Ambient Temp. Range: Amps:

Industrial, Food Processing, Food Service, Retail, Application:

Hospitality, General Lighting

Recessed Double Contact Ballast Type:

Base: (R17d)

Average Life Hours:

14000

Beam Angle: Battery:

Bulb: T12 Coating: Copolymer

Color: Cool White Kelvin: 4100 K

Construction: CRI: 82

Diameter: 1.50 IN Dimmable:

Effective Arc Length: Enclosure:

Environmental Conditions: Filament Type:

Finish: **Fixture Type:**

Fixture Watts: Field Wiring:

Frequency Rate: Focus:

Height: **Housing Color:**

Housing Material: Housing Finish:

Incan Wattage Equivalent: Initial Lumens: 4945

Pack By: 15 Weight: 1.067

Inventory Specification: Lamp Type: Fluorescent

Lamp Wattage: Length: 60.00 IN

Lens Material: **Light Center Length:**

Material: Mean Lumens: 4500

Mount: SDS: **Download SDS**

Number of Lamps: Operating Position:

14.25 L **Package Dimensions:** 59.50 x 8.50 x 5.25 **Package Weight:**

Power Factor: **Power Rating:**

Power Sources: Radiation Specification:

Т **Reflector Type:** Shape:

Size: **Socket Type:**

Shatter-Resistant **Special Features:** Start Type:

Style: Temperature Range:

Straight Linear Fluorescent Lamp **Total Harmonic Distortion:** Type:

UNSPSC: 39101605 UPC: 726585580132

Volts: Wattage: 75.0

Warm Up Time: Width:

01

ULEPH,ROHS,NSF Non-Food Zone,NSF Splash Zone

ProdCI: