



82537

F54T5 835/HO/ALTO (PK X 40)



Ambient Temp. Range:		Amps:	
Application:	Industrial, Food Processing, Food Service, Retail, Hospitality, General Lighting	Average Life Hours:	24000
Ballast Type:		Base:	Miniature Bi-Pin (G5)
Battery:		Beam Angle:	
Bulb:	T5	Coating:	Copolymer
Color:	835	Kelvin:	3500 K
Construction:		CRI:	85
Diameter:	0.63 IN	Dimmable:	
Effective Arc Length:		Enclosure:	
Environmental Conditions:		Filament Type:	
Finish:		Fixture Type:	
Fixture Watts:		Field Wiring:	
Focus:		Frequency Rate:	
Height:		Housing Color:	
Housing Material:		Housing Finish:	
Incan Wattage Equivalent:		Initial Lumens:	5000
Pack By:	40	Weight:	0.335
Inventory Specification:		Lamp Type:	Fluorescent
Lamp Wattage:		Length:	46.00 IN
Lens Material:		Light Center Length:	
Material:		Mean Lumens:	4450
Mount:		SDS:	Download SDS
Number of Lamps:		Operating Position:	
Package Dimensions:	46.75 x 6.75 x 4.25	Package Weight:	14.55 L
Power Factor:		Power Rating:	
Power Sources:		Radiation Specification:	
Reflector Type:		Shape:	T
Size:		Socket Type:	
Special Features:	Shatter-Resistant	Start Type:	
Style:		Temperature Range:	
Total Harmonic Distortion:		Type:	Straight Linear Fluorescent Lamp

UNSPSC:	39101605	UPC:	726585825370
Volts:	120	Wattage:	54.0
Width:		Warm Up Time:	
ProdCI:	01		

ULEPH,ROHS,NSF Non-Food Zone,NSF Splash Zone