



| | | | |
|----------------|--|--------------|--|
| Project | | Date | |
| Type | | Notes | |

Linear Pro LED Large Area Light

The Ironclad® Linear Pro fixture is designed to withstand abuse and drastically delay, tampering, removal or damaging of a light fixture within the prison facility. The unique design completely eliminates the metal housing in current style fixtures which can be used to make weapons. The fixture uses a specially engineered .5" thick steel frame and proprietary .5" thick cast low profile lens. There is no areas to hide contraband or open the fixture. The optional count light LED module can be turned on and off as needed depending on the application of the area being used.

Construction

Lens - Highly impact-resistant 1/2" thick urethane with a minimum IK10 impact rating

Installation - Anchored flush onto ceiling with (8) spike anchors or optional recessed tamper-proof 1/4" stainless steel bolts or cinder block fasteners

Features - No accessible parts or hinges
- No maintenance needed


Specifications

- Extreme Durability - hammer & knife tested.
- No areas to hide or conceal contraband.
- Dimensions: 25.8" long x 9" wide x 1.8" tall



| | |
|---------------------------|--|
| Watts | 40W, 80W |
| Voltage | 120-277V |
| Lumens | 4200, 8400 Count Light: 530 |
| Color Temperatures | 5000K, 4000K Count Light: 2700K |
| LED Life | L70>75,000 Hours; Projected>100,000 Hours |
| Footcandles | 35 ftc at the desk level; 22 ftc at the floor |
| Warranty | 5 year limited warranty |



 Manufactured in America with globally and domestically sourced components

Ordering Guide

| Wattage | Fixture | CCT | Mount | Count Light | Voltage | Frame | Lens | Access. | Access. | Access. | Rev |
|-----------|-----------------|------------|-------------|-------------|---------------|--------------------------|---------------|----------------------|-----------------------------------|-----------------------------|-----------|
| | LR | | CM | | VH | | UR | | | | 01 |
| 040 = 40W | LR = Linear Pro | 50 = 5000K | CM = Center | Y = Yes | VH = 120-277V | S1 = Powder Coat, Black | UR = Urethane | 00 = None | 00 = None | 00 = None | |
| | | | | | | S2 = Powder Coat, White | | JB = Surface Box Kit | TB = Tamper-proof Bolts & Inserts | | |
| 080 = 80W | | 40 = 4000K | | N = No | | S3 = Powder Coat, Bronze | | CB = Corner Box Kit | SA = Spike Anchors | CF = Cinder Block Fasteners | |
| | | | | | | | | HD = Hammer Drive | | | |