



<b>Project</b>		<b>Date</b>	
<b>Type</b>		<b>Notes</b>	

## VR Pro™ Vandal-Resistant LED Correctional Cell Light

The Ironclad® VR Pro Vandal-Resistant correctional cell and behavioral room fixture uses an LED high efficiency light engine with a light that simulates daylight. The incorporated count light LED module gives off a soothing warm light that can be turned on and off as needed.

### Construction

**One piece Mounting Ring** - .500" thick 304 Stainless Steel

**Lens** - .400" thick cast, diffused translucent, Highly Engineered Polyurethane. Shore hardness D80+, tensile strength 5,400 psi, impact strength 55 in. lbs./ in.

**Mounting** - .125" aluminum heat sink to maintain thermal management


**Installation** - Anchored flush onto ceiling with (8) recessed tamper-proof 1/4" concrete drive anchors or (8) 1/4" tamper-proof stainless steel bolts

**Wiring** - Hard wired direct to AC current; eliminating failure points via driver

**Features** - No accessible parts, No rusting or peeling paint, Count Light

### Specifications

- Extreme Durability - hammer & knife tested.
- No areas to hide or conceal contraband.
- Weight: 7.9 lbs.
- Dimensions: 12.25" diameter x 1.9" tall



<b>Watts</b>	35W or 42W
<b>Voltage</b>	120 or 277V
<b>Lumens</b>	3,600
<b>Color Temperatures</b>	5000K, 4000K, 3500K or 2700K; Count Light 2700K
<b>LED Life</b>	L70>75,000 Hours; Projected>100,000 Hours
<b>Footcandles</b>	35 ftc at the desk level; 22 ftc at the floor
<b>Warranty</b>	5 year limited warranty



Manufactured in America with globally and domestically sourced components

### Ordering Guide

Wattage	Fixture	CCT	Mount	Count Light	Voltage	Ring Material	Lens	Access.	Access.	Access.	Rev
	VR									00	01
042 = 42W	VR = Vandal Resistant	50 = 5000K	CL = Ceiling	Y = Yes	VH = 120-277V	SS = 304 Stainless	UR = Urethane	00 = None	00 = None	00 = None	
		40 = 4000K	WL = Wall			TB = Tamper-proof Bolts & Inserts					
						35 = 3500K	FT = Flat Top		N = No		
035 = 35W		27 = 2700K	FW = Flat Wall	P5 = Powder Coat, SS, Brown		JB = Surface Box Kit	SA = Spike Anchors				
							MS = Metal Ceiling Screws				